Thin Client Technology At Its Peak

Part Number: 5416v

RBT 416v thin client

Value Class Thin Client

The RBT-416v Thin Client is designed for a desktop virtualization (VDI) environment. Complete with VMware View with PCoIP, Citrix XenDesktop, 2X VirtualDesktopServer, Quest/Provision Networks vWorkspace, Leostream Connection Broker and Ericom PowerTerm WebConnect, this unit offers increased flexibility and a complete desktop experience.

The RBT-416v is an affordable, energy efficient, compact thin client. Assembled in the USA, this unit weighs just over 1lb. allowing flexible mounting options and low shipping costs. The RBT-416v has no moving parts and consumes only 8-9 watts of energy.

Windows Embedded Standard 2009	Centralized Management
Small Form Factor for Space-Saving	Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 and Cisco Compliant
Multiple Level Lock Down Feature with Protected File System	Wide Screen Support
IE8	1600 X 1200 Maximum Resolution
Supports RDP, ICA and VDI Deployment	Built-in Kensington Security Lock
Energy Efficient (Only 8-9 Watts)	RoHS and Engery Star Compliant
Designed for Virtual Desktop Deployment	VESA Mounting Capability

Reduce IT Costs, Increase Security and Improve Efficiency by Switching to 10ZiG Thin Clients

10ZiG Technology • 23309 N 17th Drive, #100, Phoenix, AZ 85027
P: 866-865-5250 • **F:** 623-516-8697 • **E:** info@10zig.com • **W:** www.10zig.com

RBT-416v thin client

System

Operating System	Windows Embedded Standard 2009
Form Factor	Compact case
Management	10ZiG Management Software
Processor	VIA 400MHz
Browser	IE8
Video Resolution	Up to 1600 x 1200 x 32 bit color
Wide Screen Support	●

Memory

RAM (Stand/MAX)	512MB/1GB
Storage (Stand/MAX)	1GB/1GB

Software Configuration

ICA	Version 11 with HDX
RDP	7
Client Software	Windows Media Player 11
	Adobe Flash Player 10
	Shockwave 11.5
	Sun JVM 1.6 & MS Java
	VNC Shadowing
	ThinPrint.print
VDI Clients	Quest vWorkspace V6.2, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View 4 with PCoIP and 2X VirtualDesktopServer

Dimensions

Device	1.4" W x 6.1" H x 4.8" D 36mm x 156 mm x 122 mm
Weight	1.7 lbs. (0.75kg)

Audio

Mic In/Line Out	●
Speaker	x 1 (built-in 1W internal Speaker)

Management

10ZiG Remote Manager	●
Various Client Configurations	●
Shadow Terminals	●
Status Indication	●
Power on, Log off, Reboot and Shut down	●
Task Scheduler	●
Cloning of Terminals	●
Group Operations	●
Update of Firmware	●
Recover Image	●

Ports

USB Ports Type 2	x4
PS2 Port	●

Environmental

Operating Temperature	0° ~ 35°C 32° ~ 95°F
Operating Humidity	20% ~ 80% non-condensing

Power

Consumption	8 - 9 watts average
AC/DC Adapter	Included

Networking

	Autosensing, 10/100 Ethernet, RJ-45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option

Compliance

	RoHS
	WEEE
	CE
	FCC
	Energy Star Compliant

Features

Security Features	Kensington Security Lock Slot
	Auto start/auto-restart connection, Multiple level lock-down user interface
	Administrative and user passwords
Language Support	US, UK English, German, French, Swedish and others by request

Ordering Information

PID	Description
5416v	RBT 416v, XPe, IE8, RDP, ICA, Flash Player, Shockwave, Windows Media Player, Sun JVM & MS Java, VDI Clients and Optical Mouse
9001	USB to Centronics
9004	VESA Mounting Bracket (with short VGA cable)
9009	Internal Wireless (802.11 b/g)
9010	Internal Wireless (802.11 b/g/n + Cisco)
8104b	104-Key PC Keyboard

10ZiG Technology ● 23309 N 17th Drive, #100, Phoenix, AZ 85027
P: 866-865-5250 ● **F:** 623-516-8697 ● **E:** info@10zig.com ● **W:** www.10zig.com