

## Overview

The 10ZiG Point-of-Service Handhelds provide the precise features needed to streamline operations and improve productivity, data accuracy, and service. The 435 Handheld POS features a 3.5" outdoor-viewable display and magnetic stripe reader in a compact and lightweight package. With numeric keyboard, integrated Bluetooth and IrDA connectivity, and optional barcode scanner or RFID reader module, the 435 enables efficient point-of-service applications, inventory management, and field services. IP54 rated for liquid and dust resistance, this POS handheld performs well indoors, outdoors, and in harsh environments.

## Features

- 3.5" VGA/ QVGA TFT-LCD touch screen
- Outdoor-viewable display
- Integrated magnetic stripe reader (MSR)
- Slim and lightweight design
- 21-key numeric keypad
- Support for Windows® CE 6.0
- IP54 rated; for dust and water resistance
- WLAN, built-in Bluetooth, and IrDA connectivity
- Extended operation through hot-swappable battery packs (4-6 Hours)
- Optional integrated 1D/ 2D barcode scanner or RFID reader
- RDP & ICA



## Applications

The 10ZiG Handheld POS is ideal for many point-of service applications, such as:

- Healthcare
- Inventory and Warehouse
- Manufacturing
- Hospitality
- Retail



## Major Options

- Optional RFID or 1D/2D barcode scanner



## System

<b>Processor</b>	ARM 533 MHz
<b>Display</b>	3.5" VGA/ QVGA TFT-LCD touch screen (outdoor viewable)
<b>Display resolution</b>	272 x 480 Pixel
<b>Memory</b>	128MB Mobile SDRAM, 128MB Flash ROM
<b>Operating System</b>	Microsoft Windows CE 5.0
<b>Integrated Radio/communication</b>	IrDA, IEEE 802.11 b/g WLAN, and Bluetooth 2.0 (without EDR); Optional RFID
<b>Control Switch &amp; Buttons</b>	1 power button; 4 front programmable; 2 trigger buttons (programmable)
<b>Input/Output Ports</b>	1 Headphone jack, 1 USB 1.1 port, 1 cradle interface, 1 DC-in jack
<b>Speaker</b>	1 built-in speaker
<b>Microphone</b>	1 mono microphone
<b>Mechanical and Environment</b>	
<b>Dimensions (HxWxD)</b>	6.3 x 3.4 x 1.2 (in); 160 x 86 x 30 (mm)
<b>Weight</b>	0.9 lbs (415 g)
<b>Rain and Dust Resistance</b>	IP54
<b>Temperature</b>	Operating: 0° ~40°C; Storage: 0°~60°C
<b>Humidity</b>	0%~90% non-condensing