Thin Client Technology At Its Peak

Part Number: 7972v

LTC 1300v thin client

Enterprise Class Thin Client

The **LTC 1300v** Thin Client is designed for a desktop virtualization (VDI) environment. Complete with VMware View, Citrix XenDesktop, 2X VirtualDesktopServer, Quest vWorkspace, Leostream Connection Broker and Ericom PowerTerm Web Connect, this unit offers increased flexibility and a complete desktop experience.

The LTC 1300v is available with an 802.11 b/g/n internal wireless option. The built in PCI and PCMCIA expansion slots can provide capability for WiFi.

The **LTC 1300v** supports two modes of operation:

WBT Mode	Windows based Terminal mode, where the terminal behaves like a CE.NET device with full screen applications, Terminal Server access, Citrix or VDI which auto start and auto reconnect.
Kiosk Mode	Dedicated Kiosk type of interface not configurable by the user of the terminal.

Reduce IT Costs, Increase Security and Improve Efficiency by Switching to 10ZiG Thin Clients

✔ Linux Operating System	✔ Centralized Management
✔ No Moving Parts	✔ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 Personal/Enterprise
✔ Read Only File System	✔ Wide Screen Support
✔ Embedded Firefox Broswer	✔ 1600 X 1200 Maximum Resolution
✔ Supports RDP, ICA and VDI Deployment	✔ Built in Kensington Security Lock
✔ Energy Efficient (Only 15 Watts)	✔ RoHS Compliant
✔ Designed for Virtual Desktop Deployment	✔ Mounting Capability
✔ Open Office & Skype Capabilities	✔ Cisco VPN

10ZiG Technology . 2012 W. Lone Cactus Dr, Phoenix AZ 85027
P: 866-865-5250 . F: 623-516-8697 . E: info@10zig.com . W: www.10zig.com

LTC 1300v thin client

System

Operating System	Linux 2.6 Kernel
Form Factor	Compact case
Management	10ZiG Management Software
Processor	VIA 1.5 GHz
Browser	Firefox 3.0
Video Resolution	8X AGP Up to 1600 x 1200 x 32 bit color
Wide Screen Support	●

Memory

RAM (Stand/MAX)	512MB/1GB
Storage (Stand/MAX)	512MB/1GB

Software Configuration

ICA	Version 11 with HDX
RDesktop	1.5
Client Software	Adobe Flash Player 10
	Sun JVM 1.6
	VNC Shadowing
	Cisco VPN
	Linux PN Agent
	NX Client
	Skype
	Open Office
VDI Clients	Quest vWorkspace V6.2, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View V3.1 and 2X VirtualDesktopServer

Dimensions

Device	2" W x 11.5" H x 8.2" L 53 mm x 292 mm x 237 mm
Weight	8.4 lbs. (3.8kg)

Audio

Mic In/Line Out	●
Speaker	x 1 (built in 1W internal Speaker)

Management

10ZiG Remote Manager	●
Various Client Configurations	●
Shadow Terminals	●
Status Indication	●
Power on, Log off, Reboot and Shut down	●
Task Scheduler	●
Cloning of Terminals	●
Group Operations	●
Update of Firmware	●

Ports

USB Ports Type 2	4
PS2 Port	●
Serial Port (D Sub, 9 Pin Male Connector)	2
Parallel Port (D Sub, 25 Pin Female Connector)	1

Environmental

Operating Temperature	0° ~ 40°C 32° ~ 104°F
Operating Humidity	20% ~ 90% non condensing

Power

Consumption	15 watts average
AC/DC Adapter	Included

Networking

	Autosensing, 10/100 Ethernet, RJ 45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option

Compliance

	RoHS
	WEEE
	CE
	FCC

Features

Security Features	Kensington Security Lock Slot
	Auto start/auto restart connection, Lock down user interface
Language Support	US, UK English, German, French, Swedish and others by request

Ordering Information

PID	Description
7972v	LTC 1300v, linux, RDesktop, ICA, VDI Clients and Optical Mouse
8012	Mounting Bracket
9009	Internal Wireless (b/g)
9010	Internal Wireless (b/g/n)
8104b	104 Key PC Keyboard

10ZiG Technology . 2012 W. Lone Cactus Dr, Phoenix AZ 85027
P: 866-865-5250 . F: 623-516-8697 . E: info@10zig.com . W: www.10zig.com