



Part Number: 5416

RBT 416 thin client *Value Class Thin Client*

The RBT-416 is an affordable, energy efficient, compact thin client. Assembled in the USA, this unit weighs just over 1lb. allowing flexible mounting options and low shipping costs. The RBT-416 has no moving parts and consumes only 8-9 watts of energy.



| | |
|---|---|
| ✓ XPe Operating System | ✓ Centralized Management |
| ✓ Small Form Factor for Space-Saving | ✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 and Cisco Compliant |
| ✓ Multiple Level Lock Down Feature with Protected File System | ✓ Wide Screen Support |
| ✓ IE6 (**IE7/8 upon request) | ✓ 1600 X1200 Maximum Resolution |
| ✓ Supports RDP, ICA and VDI Deployment | ✓ Built-in Kensington Security Lock |
| ✓ Energy Efficient (Only 8-9W) | ✓ RoHS and Energy Star Compliant |
| ✓ BOSaNOVA Secure 5250 Emulation | ✓ VESA Mounting Capability |

***Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients***





System

| | |
|----------------------------|---|
| Operating System | XPe SP2 (Windows Embedded Standard 2009 available upon request) |
| Form Factor | Compact case |
| Management | 10ZiG Management Software |
| Processor | VIA 400MHz |
| Browser | IE6 (**7 or 8 available upon request) |
| Video Resolution | Up to 1600 x 1200 x 32 bit color |
| Wide Screen Support | • |

Memory

| | |
|----------------------------|-----------|
| RAM (Stand/MAX) | 512MB/1GB |
| Storage (Stand/MAX) | 512MB/8GB |

Software Configuration

| | |
|--------------------------------------|---|
| Host Access (BOSaNOVA Secure) | Supports TN5250e, SSL and SSO |
| ICA | Version 11 with HDX |
| RDP | 6.1 (RDP 7 available on WES) |
| Client Software | Adobe Acrobat Viewer 7 (**8 or 9 available upon request) Adobe Flash Player 10 MS Office Viewers 2003 (2007 available upon request) Microsoft Outlook Express Windows Media Player 11 Shockwave 11.5 Sun JVM 1.42 (1.6 upon request) & MS Java VNC Shadowing |
| VDI Clients | Optional Quest vWorkspace V6.2, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View 4 with PCoIP and 2X VirtualDesktopServer |

Dimensions

| | |
|---------------|--|
| Device | 1.4" W x 6.1" H x 4.8" D 36mm x 156 mm x 122 mm |
| Weight | 1.7 lbs. (0.75kg) |

Audio

| | |
|------------------------|------------------------------------|
| Mic In/Line Out | • |
| Speaker | x 1 (built-in 1W internal Speaker) |

Management

| | |
|---|---|
| 10ZiG Remote Manager | • |
| Various Client Configurations | • |
| Shadow Terminals | • |
| Status Indication | • |
| Power on, Log off, Reboot and Shut down | • |
| Task Scheduler | • |
| Cloning of Terminals | • |
| Group Operations | • |
| Update of Firmware | • |
| Recover Image | • |
| Configuration of Various Connection Types including 5250 | • |

Ports

| | | |
|------------------|---------------|----|
| USB Ports | Type 2 | x4 |
| PS2 Port | | • |

Environmental

| | |
|------------------------------|--------------------------|
| Operating Temperature | 0° ~ 35°C 32° ~ 95°F |
| Operating Humidity | 20% ~ 80% non-condensing |

Power

| | |
|----------------------|---------------------|
| Consumption | 8 - 9 watts average |
| AC/DC Adapter | Included |

Networking

| | |
|--|---|
| | Autosensing, 10/100 Ethernet, RJ-45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option |
|--|---|

Compliance

| | |
|--|-----------------------|
| | RoHS |
| | WEEE |
| | CE |
| | FCC |
| | Energy Star Compliant |

Features

| | |
|--------------------------|---|
| Security Features | Kensington Security Lock Slot Auto start/auto-restart connection, Multiple level lock-down user interface Administrative and user passwords |
| Language Support | US, UK English, German, French, Swedish and others by request |

Ordering Information

| PID | Description |
|---------------|---|
| 5416NE | RBT 416, XPe, IE6 SP2, Sun JVM & MS Java, RDP, ICA, Shockwave, Flash Player, Optical Mouse, Adobe Acrobat Viewer, MS Office Viewers, MS Outlook Express and Windows Media Player. |
| 5416 | Featured software from 5416NE plus BOSaNOVA Secure 5250 Emulation |
| 9001 | USB to Centronics |
| 9004 | VESA Mounting Bracket (with short VGA cable) |
| 9010 | Internal Wireless (802.11 b/g/n + Cisco) |
| 8122b | 122-Key Driverless PC Keyboard |
| 8104b | 104-Key PC Keyboard |

** Requires IE 7, Sun JVM 1.6, Adobe 8 or 9
1GB DOM

*VT320, VT420, VT52, WYSE60, WYSE60/AIF, VAX/AIX, LINUX, HP70094/8, HP70092/6, HP2392A

