

4548 Series Zero Clients 4K Value & Security Class

Model Numbers: 4548v, 4548c, 4548r, 4548p

Industry Leading VDI Performance

The 4548 Series is a new, highly secure model to the 10ZiG product lineup. The 4548 Series is small in size yet surprisingly powerful, supporting a 4K dual monitor setup at a value price point. Featuring a 1 x DisplayPort and 1 x HDMI combination along with a rare industry find of a Fiber option, the 4548 Series is an ideal choice for Federal and Military as well as Enterprise Organizations in verticals such as Finance and Healthcare needing the absolute highest levels of security in their VDI environment.

The 10ZiG 4548 NOS™ Series Zero Client is available as a VMware, Citrix, RDP or Parallels RAS Zero Client supporting Blast Extreme, PCoIP, & HDX and has the ability to transform between all solutions with a simple firmware upgrade.



▶ Intel Dual Core N3060 1.6 GHz (2.48 GHz Burst Frequency)
▶ Optional Fiber
▶ 1 x DisplayPort and 1 x HDMI combination
▶ 5 x USB (2 x USB 3.0)
▶ Optional Wireless (External Antenna)
▶ Optional VESA and ARM Mount
▶ Optional TAA Compliance & TPM 2.0 (Windows Only)
▶ 4K UHD with Dual Monitor Support*
▶ 802.1x Network Authentication
▶ FREE Endpoint Management via The 10ZiG Manager™



4548 Series Zero Clients



System	
Management	10ZiG Manager
Form Factor	Ultra Mini
Processor	Intel Dual Core N3060 1.6 GHz (2.48 GHz Burst Frequency)
Processor Graphics	Intel HD Graphics
Dimensions	
Device	5.5"(D) x 2.4"(W) x 6.6"(H) - 140mm x 61mm x 168mm
Weight	1.39 lbs (630g)
Connections	
Ports	1 x DisplayPort, 1 x HDMI, 2 x USB 3.0, 3 x USB 2.0, 1 x Mic In, 1 x Line Out, 1 x LAN (RJ45 or Fiber option), DC Jack
Video/Resolution	3840 x 2160 @ 30Hz / 2560 x 1600 @ 60Hz (2 monitors at 4K UHD)
Networking	
Wireless	Optional (802.11 a/b/g/n/ac External Antenna)
Fiber OR Ethernet	Fiber option OR standard RJ45 LAN (10/100/1000 Base-T)
Environmental	
Operating Temp.	32°-95°F (0°-35°C), 20-80% non-condensing humidity
Power	3-4 Average Watt Consumption, DC-12V/2A External Power Adapter

SPECIFICATIONS

- | | |
|--------------------------------------|-------------------------------|
| 1. Power Button | 7. HDMI Port |
| 2. USB 3.0 (2) | 8. DisplayPort |
| 3. Mic In | 9. RJ45 LAN or Fiber LAN Port |
| 4. Line Out | 10. DC Jack |
| 5. Reserve hole for external antenna | 11. Kensington Lock |
| 6. USB 2.0 (3) | |

VMware
4548v

Citrix
4548c

RDP
4548r

Parallels RAS
4548p

Operating System NOS™ (Zero) NOS™ (Zero) NOS™ (Zero) NOS™ (Zero)



Memory (RAM)	Std: 2GB Max: 8GB	Std: 2GB Max: 8GB	Std: 2GB Max: 8GB	Std: 2GB Max: 8GB
--------------	----------------------	----------------------	----------------------	----------------------



VDI Broker Support	VMware Horizon (Blast Extreme, PCoIP, RDP)	Citrix XenApp & XenDesktop	RDP	Parallels RAS
--------------------	---	----------------------------	-----	---------------

*4K performance dependent upon your current VDI Infrastructure and the necessary minimum requirements to support it.



Americas P: +1 (866) 865-5250
 EMEA P: +44 (0) 116 214 8650
 APAC P: +61 2 80027421
 DE P: +49(0) 6724 9304 45

E: info@10ZiG.com
 E: info@10ZiG.eu
 E: info@10ZiG.com.au
 E: vertrieb@10zig.de

W: www.10ZiG.com

