

6048q Series Zero Clients

Model Numbers: 6048qv, 6048qc, 6048qm

Industry Leading Endpoints & Management for VDI

The 10ZiG 6048q Series is a flexible, powerful workhorse Zero Client addition to the 10ZiG product lineup. A compact, durable, reliable, and fanless endpoint, the 6048q is Fiber Optional and features an innovative optional I/O expansion via Port-on-Foot design. Equipped with free centralized management via The 10ZiG Manager™, which comes cloud-enabled with unlimited user licenses. Covered by a 3-Year Advance Warranty, technical support, and software upgrades. Also available in a Thin Client device.



- ▶ Intel J4105 Quad Core 1.5GHz (2.5GHz Burst)
- ▶ 2 x DisplayPort (3840 x 2160), 4K @ 60Hz
- ▶ 1 x DDR4 RAM for High Speed Support
- ▶ 4 x USB Port 2.0, 1 x USB Port 3.0, 1 x USB Port C
- ▶ RJ45 LAN (Optional Fiber LAN)
- ▶ Optional TPM 2.0
- ▶ Optional TAA Compliant
- ▶ Optional Wireless (Dual External Antenna)
- ▶ Supports VESA Mount and Kensington Lock
- ▶ FREE Centralized Management via The 10ZiG Manager™

6048q Series Zero Clients



System	
Management	The 10ZiG Manager™
Form Factor	Mini
Processor	Intel J4105 Quad Core 1.5GHz (2.5GHz Burst)
Processor Graphics	Intel HD Graphics
Dimensions	
Device	1.7" (D) x 6.0" (W) x 7.9" (H) in.
Weight	3.53 lbs. (1.6 kg.)
Connections	
Ports on Device	2 x DisplayPort, 4 x USB Port 2.0, 1 x USB Port 3.0, 1 x USB Port C, 1 x Mic-In, 1 x Line-Out, 1 x DC Jack
Port-on-Foot Options	1 x COM + 1 x Parallel Port
Video Resolution	2 x (3840 x 2160) @ 60Hz (2 Monitors at 4K UHD)
Networking	
Wireless	Optional (802.11 a/b/g/n/ac External Antenna)
Ethernet	10/100/1000 Base-T, RJ45 LAN or Fiber Optional
Environmental	
Operating Temp.	32°-95°F (0°-35°C), 20-80% non-condensing humidity



SPECIFICATIONS

1. Power Button/Power LED
2. USB Type C
3. USB 3.0
4. Mic-In
5. Line-Out
6. Antenna Holes
7. USB 2.0
8. DisplayPorts
9. RJ45 LAN/Fiber LAN
10. 12V DC Jack
11. Kensington Lock Slot
12. Optional Port-on-Foot

	<u>VMware</u> 6048qv	<u>Citrix</u> 6048qc	<u>Microsoft</u> 6048qm
Operating System	NOS™ (Zero)	NOS™ (Zero)	NOS™ (Zero)
Memory (RAM)	Std: 4GB Max: 8GB	Std: 4GB Max: 8GB	Std: 4GB Max: 8GB
Supported Protocols	Blast Extreme, PCoIP, RDP	Citrix ICA and EDT (HDX)	Azure Virtual Desktop (formerly Windows Virtual Desktop), RDP
Connection Server	Horizon, Workspace One, Horizon Security Server, Unified Access Gateway	Storefront, Netscaler, Citrix Cloud	Direct RDP, RD Gateway, RD Load Balancer, RD Web

Note: 4K performance dependent upon your current VDI Infrastructure and the necessary minimum requirements to support it.

