

7700q Series Thin Clients AIO Power Class

Model Numbers: 7772q, 7710q

Industry Leading VDI Performance

The 7700q Series is the newest model to the 10ZiG product lineup with its ultra-slim, stylish, 23.8" Full HD Display with LED backlight panel and two external up to 4K display monitor support with incredible all-in-one convenience and powerful performance. The new 10ZiG 7700q Series is based on a fanless Intel Braswell x5-E8000 Quad-Core 1.04 GHz/2.00 GHz Burst CPU platform. The sturdy compact foot stand is a strong anchor-base that tilts from -5 to 20 degrees and swivels an impressive -65 to 65 degrees.

The slender 9.9mm, frameless bezel design of the 10ZiG 7700q Series offers a 250 nits and anti-Glare panel for super-comfortable reading, OSD multiple-support control button functionality, and enables lower power consumption - on average equal to or less than 20 W.



- ▶ Quad-Core Intel Braswell x5-E8000 Processor
- ▶ Operates at a Base Frequency of 1.04 GHz (2.00 GHz Burst)
- ▶ 23.8" Full HD Display with LED backlight panel (1920 x 1080)
- ▶ 2 x External up to 4K Display Monitor Support (1920 x 1080 DVI-D & 3840 x 2160 @30Hz DP)
- ▶ 4 x USB (2 x USB 3.0)
- ▶ Optional Wireless
- ▶ Optional TAA Compliance
- ▶ 802.1x Network Authentication
- ▶ FREE Centralized Mgmt. via 10ZiG Manager



Americas
EMEA
APAC
DE

P: +1 (866) 865-5250
P: +44 (0) 116 214 8650
P: +61 2 80027421
P: +49(0) 6724 9304-45

E: info@10ZiG.com
E: info@10ZiG.eu
E: info@10ZiG.com.au
E: vertrieb@10zig.de

W: www.10ZiG.com

7700q Series Thin Clients



System	
Management	10ZiG Manager
Form Factor	All-in-One
Processor	Intel Braswell x5-E8000 Quad-Core 1.04 GHz (2.00 GHz Burst Frequency)
Processor Graphics	Intel HD Graphics for Intel® Celeron® Processor N3000 Series
Dimensions	
Device	54 x 32.4 x 4.2 cm (21.2 x 12.6 x 1.6 inch) (w/o stand)
Weight	4.5kg
Connections	
Ports	2 x USB 2.0, 2 x USB 3.0, 1 x Mic In, 1 x Line Out, DVI-D output, DP output, 1 x GbE LAN, 2 x Speaker
Video/Resolution	1920 x 1080 supporting 2 x External Monitors (1920 x 1080 DVI-D & 3840 x 2160 @30Hz DP) *
Networking	
Wireless	Optional (802.11 a/b/g/n/ac External Antenna)
Ethernet	X 1 (RJ-45, 10/100/1000 Base-T)
Environmental	
Operating Temp.	32° to 95° F (0° to 35° C)
Power	19V 65W or 60W

7772q

7710q

Operating System

PeakOS™ (Linux)

Windows 10 IoT

Memory		
RAM	Std: 2GB Max: 8GB	Std: 4GB Max: 8GB
Storage		
Storage	Std: 8GB Max: 256GB	Std: 16GB Max: 256GB
Software		
Software Applications	Firefox, Google Chrome**, Adobe Reader, Putty, Citrix Receiver, VMware Horizon Client, FreeRDP Client, Parallels Client, VNC (Shadowing), GStreamer, OpenOffice**, iSeries/5250 Emulation**, JRE (Java Runtime Engine)	Internet Explorer, Citrix Receiver, RDP, VMware Horizon Client, VNC (Shadowing), Windows Media Player, Amazon WorkSpaces Client**, Parallels RAS Client, Spice Client, JRE (Java Runtime Engine), Microsoft Silverlight, Workspot Client
VDI Connection Brokers Supported	VMware Horizon (Blast Extreme/PCoIP/RDP), Citrix XenApp & XenDesktop (HDX/HDX Premium/HDX 3D Pro), RDP, Parallels RAS	VMware Horizon (Blast Extreme/PCoIP/RDP), Citrix XenApp & XenDesktop (HDX/HDX Premium/HDX 3D Pro), RDP, Parallels RAS, Workspot VDI, Amazon WorkSpaces (AWS)

*4K performance dependent upon your current VDI infrastructure and the necessary minimum requirements to support it.

**Optional Application may require alternative model; please speak to a sales representative to confirm.



Americas P: +1 (866) 865-5250
 EMEA P: +44 (0) 116 214 8650
 APAC P: +61 2 80027421
 DE P: +49(0) 6724 9304-45

E: info@10ZiG.com
 E: info@10ZiG.eu
 E: info@10ZiG.com.au
 E: vertrieb@10zig.de

W: www.10ZiG.com

