

### 4548 Series Zero Clients

Model Numbers: 4548v, 4548c, 4548m

### Industry Leading Endpoints & Management for VDI

The 10ZiG 4548 Series is a secure, powerful, choice endpoint ideal for federal, military, and enterprise organizations like finance and healthcare, needing the highest levels of security. Comes with 4K dual monitor support and rare Fiber option at a value cost. Supportive of VMware, Citrix, Microsoft, Parallels, Amazon WorkSpaces, and more. Equipped with free centralized management via The 10ZiG Manager™, which comes cloud-enabled with unlimited user licenses. Covered by a 3-Year Advance Warranty, technical support, and software upgrades. Also available in a Thin Client device.



▶ Intel Dual Core N3060 1.6GHz (2.48GHz Burst)
▶ 4K UHD with Dual Monitor Support*
▶ 2 x USB Port 3.0, 3 x USB Port 2.0
▶ RJ45 LAN (Optional Fiber LAN)
▶ Optional TAA Compliant
▶ Optional TPM 2.0 (Windows Only)
▶ Optional Wireless (External Antenna)
▶ Support VESA Mount and Kensington Lock
▶ FREE Centralized Management via The 10ZiG Manager™

# 4548 Series Zero Clients



System	
Management	The 10ZiG Manager™
Form Factor	Ultra Mini
Processor	Intel Dual Core N3060 1.6GHz (2.48GHz Burst)
Processor Graphics	Intel HD Graphics
Dimensions	
Device	5.5" (D) x 2.4" (W) x 6.6" (H) in.
Weight	1.39 lbs. (0.63 kg.)
Connections	
Ports on Device	1 x DisplayPort, 1 x HDMI, 2 x USB Port 3.0, 3 x USB Port 2.0, 1 x Mic-In, 1 x Line-Out, 1 x LAN (RJ45 or Fiber option), 1 x DC Jack
Video Resolution	3840 x 2160 @ 30Hz / 2560 x 1600 @ 60Hz (2 monitors at 4K UHD)
Networking	
Wireless	Optional (802.11 a/b/g/n/ac External Antenna)
Ethernet	10/100/1000 Base-T, RJ45 LAN or Fiber Optional
Environmental	
Operating Temp.	32 ° - 95 ° F (0 ° - 35 ° C), 20-80% non-condensing humidity



### SPECIFICATIONS

1. Power Button
2. USB 3.0 (2)
3. Mic-In
4. Line-Out
5. External Antenna Hole
6. USB 2.0 (3)
7. HDMI Port
8. DisplayPort
9. RJ45 LAN / Fiber LAN
10. DC Jack
11. Kensington Lock Slot

	<u>VMware</u>	<u>Citrix</u>	<u>Microsoft</u>
	4548v	4548c	4548m
Operating System	NOS™ (Zero)	NOS™ (Zero)	NOS™ (Zero)
Memory (RAM)	Std: 2GB Max: 8GB	Std: 2GB Max: 8GB	Std: 2GB Max: 8GB
Supported Protocols	Blast Extreme, PCoIP, RDP	Citrix ICA and EDT (HDX)	Windows Virtual Desktop, RDP
Connection Server	Horizon, Workspace One, Horizon Security Server, Unified Access Gateway	Storefront, Netscaler, Citrix Cloud	Direct RDP, RD Gateway, RD Load Balancer, RD Web

Note: 4K performance dependent upon your current VDI Infrastructure and the necessary minimum requirements to support it.



Americas  
EMEA  
APAC  
DE

P: +1 (866) 865-5250  
P: +44 (0) 116 214 8650  
P: +61 2 80027421  
P: +49 (0) 6724 9304-45

E: info@10ZiG.com  
E: info@10ZiG.eu  
E: info@10ZiG.com.au  
E: vertrieb@10zig.de

W: www.10ZiG.com

