

7748q Series Zero Clients

Model Numbers: 7748qv, 7748qc, 7748qm

Industry Leading Endpoints & Management for VDI

The 10ZiG 7748q Series All-in-One is a convenient ultra-slim, stylish, 23.8" Full HD Display with LED backlight panel with two external up-to-4K display monitor support. Its compact foot stand tilts from -5 to 20 degrees and swivels an impressive -65 to 65 degrees. Equipped with free centralized management via The 10ZiG Manager™, which comes cloud-enabled with unlimited user licenses. Covered by a 3-Year Advance Warranty, technical support, and software upgrades. Also available in a Thin Client device.




- ▶ Intel Braswell x5-E8000 Quad Core 1.04GHz (2.0GHz Burst)
- ▶ AIO monitor (1920 x 1080), 2 x External Monitors (1920 x 1080 DVI-D & 3840 x 2160 @ 30Hz DP)
- ▶ 2 x USB Port 2.0, 2 x USB Port 3.0
- ▶ RJ45 LAN
- ▶ Optional TAA Compliant
- ▶ Optional Wireless (Dual External Antenna)
- ▶ Supports Kensington Lock
- ▶ FREE Centralized Management via The 10ZiG Manager™

7748q Series Zero Clients



System	
Management	The 10ZiG Manager™
Form Factor	All-in-One
Processor	Intel Braswell x5-E8000 Quad Core 1.04GHz (2.0GHz Burst)
Processor Graphics	Intel HD Graphics for Intel® Celeron® Processor N3000 Series
Dimensions	
Device	1.6" (D) x 12.6" (W) x 21.2" (H) in. (w/o stand)
Weight	9.9 lbs. (4.5 kg.)
Connections	
Ports on Device	2 x USB Port 2.0, 2 x USB Port 3.0, 1 x Mic-In, 1 x Line-Out, 1 x DVI-D output, 1 x DP output, 1 x GbE LAN, 2 x Speaker
Video Resolution	AIO monitor (1920 x 1080), 2 x External Monitors (1920 x 1080 DVI-D & 3840 x 2160 @30Hz DP)*
Networking	
Wireless	Optional (802.11 a/b/g/n/ac External Antenna)
Ethernet	10/100/1000 Base-T, RJ45 LAN
Environmental	
Operating Temp.	32°- 95°F (0°- 35°C)



SPECIFICATIONS

1. Power LED
2. OSD Control Button
3. Power Button
4. Antenna Holes
5. DVI-D Port
6. Display Port
7. USB 2.0 Port
8. RJ45 LAN
9. Mic-In
10. Line-Out
11. 19V DC Jack
12. Kensington Lock Slot
13. USB 3.0

	<u>VMware</u>	<u>Citrix</u>	<u>Microsoft</u>
	7748qv	7748qc	7748qm
Operating System	NOS™ (Zero)	NOS™ (Zero)	NOS™ (Zero)
Memory (RAM)	Std: 2GB Max: 8GB	Std: 2GB Max: 8GB	Std: 2GB Max: 8GB
Supported Protocols	Blast Extreme, PCoIP, RDP	Citrix ICA and EDT (HDX)	Azure Virtual Desktop (formerly Windows Virtual Desktop), RDP
Connection Server	Horizon, Workspace One, Horizon Security Server, Unified Access Gateway	Storefront, Netscaler, Citrix Cloud	Direct RDP, RD Gateway, RD Load Balancer, RD Web

*Note: 4K performance dependent upon your current VDI Infrastructure and the necessary minimum requirements to support it.



Americas
EMEA
APAC
DE

P: +1 (866) 865-5250
P: +44 (0) 116 214 8650
P: +61 2 80027421
P: +49 (0) 6724 9304-45

E: info@10ZiG.com
E: info@10ZiG.eu
E: info@10ZiG.com.au
E: vertrieb@10zig.de

W: www.10ZiG.com

