

6048q Series Zero Clients

Model Numbers: 6048qv, 6048qc, 6048qr, 6048qp

Industry Leading Endpoints & Management for VDI

The 10ZiG 6048q Series is a flexible, powerful workhorse Zero Client addition to the 10ZiG product lineup. A compact, durable, reliable, and fanless endpoint, the 6048q is Fiber Optional and features an innovative optional I/O expansion via Port-on-Foot design. Equipped with free centralized management via The 10ZiG Manager™, which comes cloud-enabled with unlimited user licenses. Covered by a 3-Year Advance Warranty, technical support, and software upgrades. Also available in a Thin Client device.



- ▶ Intel J4105 Quad Core 1.5GHz (2.5GHz Burst)
- ▶ 2 x DisplayPort (3840 x 2160), 4K @ 60Hz
- ▶ 1 x DDR4 RAM for High Speed Support
- ▶ 4 x USB Port 2.0, 1 x USB Port 3.0, 1 x USB Port C
- ▶ RJ45 LAN (Optional Fiber LAN)
- ▶ Optional TPM 2.0
- ▶ Optional TAA Compliant
- ▶ Optional Wireless (Dual External Antenna)
- ▶ Supports VESA Mount and Kensington Lock
- ▶ FREE Centralized Management via The 10ZiG Manager™

6048q Series Zero Clients



| System | |
|----------------------|--|
| Management | The 10ZiG Manager™ |
| Form Factor | Mini |
| Processor | Intel J4105 Quad Core 1.5GHz (2.5GHz Burst) |
| Processor Graphics | Intel HD Graphics |
| Dimensions | |
| Device | 1.7" (D) x 6.0" (W) x 7.9" (H) in. |
| Weight | 3.53 lbs. (1.6 kg.) |
| Connections | |
| Ports on Device | 2 x DisplayPort, 4 x USB Port 2.0, 1 x USB Port 3.0, 1 x USB Port C, 1 x Mic-In, 1 x Line-Out, 1 x DC Jack |
| Port-on-Foot Options | 1 x COM + 1 x Parallel Port |
| Video Resolution | 2 x (3840 x 2160) @ 60Hz (2 Monitors at 4K UHD) |
| Networking | |
| Wireless | Optional (802.11 a/b/g/n/ac External Antenna) |
| Ethernet | 10/100/1000 Base-T, RJ45 LAN or Fiber Optional |
| Environmental | |
| Operating Temp. | 32°-95°F (0°-35°C), 20-80% non-condensing humidity |



SPECIFICATIONS

1. Power Button/Power LED
2. USB Type C
3. USB 3.0
4. Mic-In
5. Line-Out
6. Antenna Holes
7. USB 2.0
8. DisplayPorts
9. RJ45 LAN/Fiber LAN
10. 12V DC Jack
11. Kensington Lock Slot
12. Optional Port-on-Foot

| | <u>VMware</u> | <u>Citrix</u> | <u>Remote Desktop</u> |
|-------------------------|---|-------------------------------------|--|
| | 6048qv | 6048qc | 6048qr |
| Operating System | NOS™ (Zero) | NOS™ (Zero) | NOS™ (Zero) |
| Memory (RAM) | Std: 4GB Max: 8GB | Std: 4GB Max: 8GB | Std: 4GB Max: 8GB |
| Supported Protocols | Blast Extreme, PCoIP, RDP | Citrix ICA and EDT (HDX) | FreeRDP |
| Connection Server | Horizon, Workspace One, Horizon Security Server, Unified Access Gateway | Storefront, Netscaler, Citrix Cloud | Direct RDP, RD Gateway, RD Load Balancer, RD Web |

Note: 4K performance dependent upon your current VDI Infrastructure and the necessary minimum requirements to support it.



Americas
EMEA
APAC
DE

P: +1 (866) 865-5250
P: +44 (0) 116 214 8650
P: +61 2 80027421
P: +49 (0) 6724 9304-45

E: info@10ZiG.com
E: info@10ZiG.eu
E: info@10ZiG.com.au
E: vertrieb@10zig.de

W: www.10ZiG.com

