

### 6000q Series Thin Clients

Model Numbers: 6072q, 6010q

### Industry Leading Endpoints & Management for VDI

The 10ZiG 6000q Series is a flexible, powerful workhorse Thin Client in the 10ZiG product lineup. A compact, durable, reliable, and fanless endpoint, the 6000q is Fiber Optional and features an innovative optional I/O expansion via Port-on-Foot design. Supportive of VMware, Citrix, Microsoft, Parallels, Amazon WorkSpaces, and more. Equipped with free centralized management via The 10ZiG Manager™, which comes cloud-enabled with unlimited user licenses. Covered by a 3-Year Advance Warranty, technical support, and software upgrades. Also available in a Zero Client device.



- ▶ Intel J4105 Quad Core 1.5GHz (2.5GHz Burst)
- ▶ 2 x DisplayPort (3840 x 2160), 4K @ 60Hz
- ▶ 1 x DDR4 RAM for High Speed Support
- ▶ 4 x USB Port 2.0, 1 x USB Port 3.0, 1 x USB Port C
- ▶ RJ45 LAN/Fiber (SFP) Ready Options
- ▶ Optional TPM 2.0
- ▶ TAA Compliant
- ▶ Optional Wireless (Dual External Antenna)
- ▶ Supports VESA Mount and Kensington Lock
- ▶ FREE Centralized Management via The 10ZiG Manager™

# 6000q Series Thin Clients



System	
Management	The 10ZiG Manager™
Processor	Intel J4105 Quad Core 1.5GHz (2.5GHz Burst)
Processor Graphics	Intel HD Graphics
Dimensions	
Device	1.7" (D) x 6.0" (W) x 7.9" (H) in.
Weight	3.53 lbs. (1.6 kg.)
Connections	
Ports on Device	2 x DisplayPort, 4 x USB Port 2.0, 1 x USB Port 3.0, 1 x USB Port C, 1 x Mic-In, 1 x Line-Out, 1 x DC Jack
Port-on-Foot Option	1 x COM + 1 x Parallel Port
Video Resolution	2 x (3840 x 2160) @ 60Hz (2 Monitors at 4K UHD)
Networking	
Wireless	Optional (802.11 a/b/g/n/ac External Antenna)
Ethernet	10/100/1000 Base-T, RJ45 LAN or Fiber LAN (SFP) Optional
Environmental	
Operating Temp.	32°-95°F (0°-35°C), 20-80% non-condensing humidity



### SPECIFICATIONS

1. Power Button/Power LED
2. USB Type C
3. USB 3.0
4. Mic-In
5. Line-Out
6. Antenna Holes
7. USB 2.0
8. DisplayPorts
9. RJ45 LAN/Fiber LAN
10. 12V DC Jack
11. Kensington Lock Slot
12. Optional Port-on-Foot

Operating System	6072q PeakOS™ (Linux)	6010q Windows 10 IoT
Memory	Std: 4GB Max: 8GB	Std: 4GB Max: 8GB
Storage	Std: 8GB Max: 256GB	Std: 32GB Max: 256GB
Software Applications	Citrix Workspace App, VMware Horizon Client, FreeRDP Client, Parallels Client, Firefox, Google Chrome*, Adobe Reader, Putty, VNC (Shadowing), OpenOffice*, iSeries/5250 Emulation*	Citrix Workspace App, RDP, Azure Virtual Desktop Client (Formerly Windows Virtual Desktop), VMware Horizon Client, Amazon WorkSpaces Client*, Workspot Client, Parallels RAS Client, Edge Browser VNC (Shadowing), 10ZiG Quick Start & UWF Wizard
Connection Servers	VMware: Horizon, Workspace One, Horizon Security Server, Unified Access Gateway Citrix: Storefront, Netscaler, Citrix Cloud RDP: Direct RDP, RD Gateway, RD Load Balancer, RD Web Parallels RAS	VMware Horizon, Workspace One, Horizon Security Server, Unified Access Gateway, Citrix Storefront, Netscaler, Citrix Cloud, Azure Virtual Desktop (Formerly Windows Virtual Desktop), Amazon Workspaces, Parallels RAS, Workspot VDI

Note: 4K performance dependent upon your current VDI Infrastructure and the necessary minimum requirements to support it.  
\*Optional Application: may require alternative model; please speak to a sales representative to confirm.