10ZiG®

Cutting Edge Thin & Zero Clients

5848q Series Zero Clients

Model Numbers: 5848qv, 5848qc, 5848qr

Industry Leading Endpoints & Management for VDI

The 10ZiG 5848q Series is where power, performance, and reliability combine to offer the most versatile Client on the market. The 5848q is ideal for knowledge workers and power users who require Full HD, Multimedia, 3D, and CAD performance. Equipped with free centralized management via The 10ZiG Manager™, which comes cloud-enabled with unlimited user licenses. Covered by a 3-Year Advance Warranty, technical support, and software upgrades. Also available in a Thin Client device.



- Intel Quad Core 2.0GHz (2.42GHz Burst)
- Choice of Dual DisplayPort or Dual DVI
- 5 x USB Port 2.0, 2 x USB Port 3.0
- RJ45 LAN
- Optional TAA Compliant
- Optional Wireless
- Support VESA Mount and Kensington Lock
- FREE Centralized Management via The 10ZiG Manager™


vmware citrix Microsoft amazon WorkSpaces teradici PCoIP

Americas P: +1 (866) 865-5250 E: info@10ZiG.com
EMEA P: +44 (0) 116 214 8650 E: info@10ZiG.eu W: www.10ZiG.com
APAC P: +61 2 80027421 E: info@10ZiG.com.au
DE P: +49 (0) 6724 9304-45 E: vertrieb@10zig.de

10ZiG

5848q Series Zero Clients

System	
Management	The 10ZiG Manager™
Form Factor	Mini
Processor	Intel Quad Core 2.0GHz (2.42GHz Burst)
Processor Graphics	Intel HD Graphics
Dimensions	
Device	5.6" (D) x 1.7" (W) x 7.1" (H) in.
Weight	2.53 lbs. (1.15 kg.)
Connections	
Ports on Device	5 x USB Port 2.0, 2 x USB Port 3.0, 1 x Mic-In, 1 x Line-Out, 1 x RJ45 LAN, 1 x DC Jack
Video Resolution	2560 x 1600, 2 x DisplayPort (or DVI option @ 1920 x 1080)
Networking	
Wireless	Optional (802.11 a/b/g/n/ac External Antenna)
Ethernet	10/100/1000 Base-T, RJ45 LAN
Environmental	
Operating Temp.	32° - 95° F (0° - 35° C), 20-80% non-condensing humidity



SPECIFICATIONS

1. Power Button/Power HD LED
2. USB 2.0 (2)
3. Mic-In
4. Line-Out
5. Secure USB 2.0
6. RJ45 LAN
7. USB 2.0 (2)
8. USB 3.0 (2)
9. DP Port - 1 (or DVI Option)
10. DP Port - 2 (or DVI Option)
11. DC Jack
12. Kensington Lock Slot

	VMware	Citrix	Remote Desktop
	5848qv	5848qc	5848qr
Operating System	**NOS™ (Zero)**	**NOS™ (Zero)**	**NOS™ (Zero)**
Memory (RAM)	Std: 2GB Max: 8GB	Std: 2GB Max: 8GB	Std: 2GB Max: 8GB
Supported Protocols	Blast Extreme, PCoIP, RDP	Citrix ICA and EDT (HDX)	FreeRDP
Connection Server	Horizon, Workspace One, Horizon Security Server, Unified Access Gateway	Storefront, Netscaler, Citrix Cloud	Direct RDP, RD Gateway, RD Load Balancer, RD Web

vmware citrix Microsoft amazon WorkSpaces teradici PCoIP

Americas P: +1 (866) 865-5250 E: info@10ZiG.com
EMEA P: +44 (0) 116 214 8650 E: info@10ZiG.eu W: www.10ZiG.com
APAC P: +61 2 80027421 E: info@10ZiG.com.au
DE P: +49 (0) 6724 9304-45 E: vertrieb@10zig.de