10ZiG®

Cutting Edge Thin & Zero Clients

6048q Series Zero Clients

Model Numbers: 6048qv, 6048qc, 6048qm

Industry Leading Endpoints & Management Software

The 10ZiG 6048q Series is a flexible, powerful workhorse Zero Client in the 10ZiG product lineup. A compact, durable, reliable, and fanless endpoint, the 6048q is Fiber Optional and features an innovative optional I/O expansion via Port-on-Foot design. Supportive of VMware, Citrix, Microsoft, Amazon WorkSpaces, and more. Equipped with free centralized management via The 10ZiG Manager™, which comes cloud-enabled with unlimited user licenses. Covered by a 3-Year Advance Warranty, technical support, and software upgrades. Also available in a Thin Client device.



- Intel Quad Core 2.00GHz (2.70GHz Burst)
- 2 x DisplayPort (3840 x 2160), 4K @ 60Hz
- Up to 8GB DDR4 RAM for High Speed Support
- 4 x USB Port 2.0, 1 x USB Port 3.0, 1 x USB Port C
- RJ45 LAN/Fiber LAN (SFP) Ready Options
- Optional TPM 2.0
- TAA Compliant
- Optional Wireless (Dual External Antenna)
- Supports VESA Mount and Kensington Lock
- FREE Centralized Management via 10ZiG Manager™

vmware citrix Microsoft amazon WorkSpaces hp teradici

Americas P: +1 (866) 865-5250 E: info@10ZiG.com
EMEA P: +44 (0) 116 214 8650 E: info@10ZiG.eu W: www.10ZiG.com
APAC P: +61 2 80027421 E: info@10ZiG.com.au
DE P: +49 (0) 6724 9304-45 E: vertrieb@10zig.de

10ZiG

6048q Series Zero Clients

System	
Management	10ZiG Manager™
Processor	Intel Quad Core 1.5GHz (2.5GHz Burst)
Processor Graphics	Intel HD Graphics
Dimensions	
Device	1.7" (D) x 6.0" (W) x 7.9" (H) in.
Weight	3.53 lbs. (1.6 kg.)
Connections	
Ports on Device	2 x DisplayPort, 4 x USB Port 2.0, 1 x USB Port 3.0, 1 x USB Port C, 1 x Mic-In, 1 x Line-Out, 1 x DC Jack
Port-on-Foot Options	1 x COM + 1 x Parallel Port
Video Resolution	2 x (3840 x 2160) @ 60Hz (2 Monitors at 4K UHD)
Networking	
Wireless	Optional (802.11 a/b/g/n/ac External Antenna)
Ethernet	10/100/1000 Base-T, RJ45 LAN or Fiber LAN (SFP) Optional
Environmental	
Operating Temp.	32°-95°F (0°-35°C), 20-80% non-condensing humidity





SPECIFICATIONS

1. Power Button/Power LED
2. USB Type C
3. USB 3.0
4. Mic-In
5. Line-Out
6. Antenna Holes
7. USB 2.0
8. DisplayPorts
9. RJ45 LAN/Fiber LAN
10. 12V DC Jack
11. Kensington Lock Slot
12. Optional Port-on-Foot

	VMware	Citrix	Microsoft
	6048qv	6048qc	6048qm
Operating System	NOS™ (Zero)	NOS™ (Zero)	NOS™ (Zero)
Memory (RAM)	Std: 4GB Max: 8GB	Std: 4GB Max: 8GB	Std: 4GB Max: 8GB
Supported Protocols	Blast Extreme, PCoIP, RDP	Citrix ICA and EDT (HDX)	Azure Virtual Desktop, RDP
Connection Server	Horizon, Workspace One, Horizon Security Server, Unified Access Gateway	Storefront, Netscaler, Citrix Cloud	Direct RDP, RD Gateway, RD Load Balancer, RD Web

Note: Actual display performance, such as multi-monitor and higher resolutions including 4K/UHD/QHD/WQHD are dependent upon your current VDI infrastructure and any additional requirements. Consult with 10ZiG for further guidance and model recommendation.

vmware citrix Microsoft amazon WorkSpaces teradici

Americas P: +1 (866) 865-5250 E: info@10ZiG.com
EMEA P: +44 (0) 116 214 8650 E: info@10ZiG.eu W: www.10ZiG.com
APAC P: +61 2 80027421 E: info@10ZiG.com.au
DE P: +49 (0) 6724 9304-45 E: vertrieb@10zig.de