Cutting Edge Thin & Zero Clients

5900q Series Thin Clients

Power Class

Model Numbers: 5972q, 5910q

Industry Leading VDI Performance

The 5900q Series Thin Client is the newest model to the 10ZiG product lineup and is of the first in the industry to fully support a triple-monitor 4K UHD setup at the absolute highest performance levels never seen before in a thin client. The new 10ZiG 5900q Series is based on the Intel Braswell Refresh CPU platform. The impressive 3840 x 2160 @ 30Hz/ 2560 x 1600 @ 60Hz support allows for a maximum of three simultaneous displays, including an in-demand 2 x DisplayPort and 1 x HDMI combination.

The CPU features the Quad-Core Intel Pentium Processor N Series N3710, has new Touch Technology with a rotating "ports-on-foot" stand, TPM 2.0 optional, and comes with a rare find of optional PoE. The 5900q Series Thin Client is available with 10ZiG PeakOS™ (Linux), Windows 10 IoT (W10 IoT) and is VMware, Citrix and Microsoft Ready.



- Quad-Core Intel Pentium Processor N Series N3710
- Operates at a Base Frequency of 1.6 GHz (2.56 GHz Burst)
- 2 x DisplayPort and 1 x HDMI Combination
- 7 x USB (2 x USB 3.0)
- Optional PoE (Power over Ethernet)
- Optional Wireless
- Optional VESA & ARM Mount
- TPM 2.0 Optional
- 4K UHD with Triple Monitor Support*
- FREE Centralized Management via 10ZiG Manager

vmware teradici PCoIP CITRIX HDX Microsoft amazon WorkSpaces

Americas P: +1 (866) 865-5250 E: info@10ZiG.com
EMEA P: +44 (0) 116 214 8650 E: info@10ZiG.eu
APAC P: +61 2 80027421 E: info@10ZiG.com.au
DE P: +49(0) 6724 934-45 E: vertrieb@10zig.de
W: www.10ZiG.com

5900q Series Thin Clients

System	
Management	10ZiG Manager
Form Factor	Mini
Processor	Intel Pentium N3710 Quad-Core 1.6 GHz (2.56 GHz Burst Frequency)
Processor Graphics	Intel HD Graphics 400
Dimensions	
Device	1.9"(W) x 7.5"(H) x 5.8"(D) I 4.9 x 19.3 x 14.9cm
Weight	1.98 lbs (900g)
Connections	
Ports	2 x DisplayPort, 1 x HDMI, 2 x USB 3.0, 5 x USB 2.0, 1 x Mic In, 1 x Line Out, 1 x LAN (RJ-45), DC Jack
Video/Resolution	3840 x 2160 @ 30Hz / 2560 x 1600 @ 60Hz (3 monitors at 4K UHD)
Networking	
Wireless	Optional (802.11 a/b/g/n/ac External Antenna)
Ethernet	1 x RJ-45 (10/100/1000 Base-T)
Environmental	
Operating Temp.	32°-95°F (0°-35°C), 20-80% non-condensing humidity
Power	3.4 Average Watt Consumption, DC-12V/3A External Power Adapter



SPECIFICATIONS

1. Power Button
2. USB 3.0 (2)
3. USB 2.0
4. Mic In
5. Line Out
6. Kensington Lock
7. USB 2.0
8. Reserve hole for extended antenna
9. USB 2.0
10. HDMI Port
11. DisplayPort (2)
12. RJ45 LAN Port
13. DC Jack

	5972q	5910q
Operating System	**PeakOS™ (Linux)**	**Windows 10 IoT**
Memory		
RAM	Std: 4GB Max: 8GB	Std: 4GB Max: 8GB
Storage	Std: 4GB Max: 256GB	Std: 16GB Max: 256GB
Software		
Software Applications	Firefox, Google Chrome**, Adobe Reader, Putty, Citrix Receiver, VMware Horizon Client, FreeRDP Client, Parallels Client, VNC (Shadowing), GStreamer, OpenOffice**, iSeries/5250 Emulation**, JRE (Java Runtime Engine)	Internet Explorer, Citrix Receiver, RDP, VMware Horizon Client, VNC (Shadowing), Windows Media Player, Amazon WorkSpaces Client**, Parallels RAS Client, Spice Client, JRE (Java Runtime Engine), Microsoft Silverlight, Workspot Client
VDI Connection Brokers Supported	VMware Horizon (Blast Extreme/PCoIP/RDP), Citrix XenApp & XenDesktop (HDX/HDX Premium/HDX 3D Pro), RDP, Parallels RAS	VMware Horizon (Blast Extreme/PCoIP/RDP), Citrix XenApp & XenDesktop (HDX/HDX Premium/HDX 3D Pro), RDP, Parallels RAS, Workspot VDI, Amazon WorkSpaces (AWS)

***4K performance dependent upon your current VDI Infrastructure and the necessary minimum requirements to support it.**
**Optional Application may require alternative model; please speak to a sales representative to confirm.

vmware teradici PCoIP CITRIX HDX Microsoft amazon WorkSpaces

Americas P: +1 (866) 865-5250 E: info@10ZiG.com
EMEA P: +44 (0) 116 214 8650 E: info@10ZiG.eu W: www.10ZiG.com
APAC P: +61 2 80027421 E: info@10ZiG.com.au
DE P: +49(0) 6724 934-45 E: vertrieb@10zig.de