1•**Z**i**G**_® V2200 Trusted Zero Client Series

AMD[®] Ryzen[™] R1305G Embedded, featuring AVX2 Support

Model Numbers: V2200, V2200S, V2203, V2200F, V2200FS

Industry Leading Trusted Zero Client by 10ZiG with PCoIP® Ultra Performance

The V2200 Series is part of the V2000 Trusted Zero Client lineup by 10ZiG with HP PCoIP® Ultra performance with support for dual display. The TAA Compliant V2200 Series provides an "ultra" secure, yet powerful and easy to manage endpoint that eliminates the chance of viruses with extensive security and authentication features. With 8GB of DDR4 RAM and supportive of 2 x DisplayPort, 5 x external USB, headphone, microphone, and internal speaker, the V2200 Series delivers a winning user experience. Options include Fiber, Wireless, Smart Card, and Vesa Mount.

Each Trusted Zero Client comes with a year of the HP Anyware Trust Center Subscription. The Anyware Trust Center Subscription enables enhanced Anyware Trust Center features, allows Trusted Zero Client firmware to be updated, and includes support from HP. Trusted Zero Clients have the ability to connect to HP Anyware, Amazon Workspaces, and VMware Horizon platforms. Trusted Zero Clients can also be managed by the FREE 10ZiG Manager[™] with unlimited licenses.*



Amazon Workspaces | Azure Virtual Desktop | Citrix | Omnissa (formerly VMware) | Windows 365 Cloud PC | HP Teradici | Nerdio | Parallels | Dizzion Frame | Inuvika | Leostream | Apporto | Workspot | Controlup | Liquidware | Imprivata | ThinPrint | 90Meter | FabulaTech

Americas EMEA APAC DF P: +1 (866) 865-5250 P: +44 (0) 116 214 8650 P: +61 2 80027421 P: +49 (0) 6724 9304 45 E: info@10ZiG.com E: info@10ZiG.eu E: info@10ZiG.com.au E: vertrieb@10ZiG.de



V2200 Trusted Zero Client ColP[®] Ultra Performance 10-2iG_®

System	
Support Subscriptions	HP Anyware Trust Center
Processor Graphics	AMD R1305G Dual Core, 1.50GHz (2.80GHz Burst)
Chipset	Radeon Vega 3, AVX2, H.264, H.265 (HEVC)
Dimensions	
Device	6.772" x 5.236" x 1.260" (w/out base)
Weight	1.41lbs. (0.64 kg.)
Connections	
Ports on Device	2 x DisplayPort, 2 x USB 2.0, 1 x USB 3.2, 1 x USB-C (Data Only) , Smart CardOption**, 1 x Mic In, 1 x Line Out
Video Resolution	2 x (3840 x 2160) @ 60Hz via DisplayPort (2 Monitors at UHD)
Networking	
Wireless	Optional (802.11ax)
Ethernet	10/100/1000 Base-T, RJ45 LAN
Fiber	Optional SFP Fiber Connector (100/1000Mbps) Environmental Operating
Environmental	
Operating Temp	32°-95°F (0°-35°C), 20-80% non-condensing humidity
Power	8-10 Watts, DC-12V/3A External Power Adapter
Certifications	

CE, FCC, IC & CAN ICES-3(B)/NMB-3(B), TELEC & VCCI, UL, TUV-GS, CCC, A-Tick/RCM, EAC, BMSI & NCC, RoHS, UKCA



V2200 Series Specifications

- Power Button/LED
- 2. Front Line Out
- 3. Mic In
- 4. USB Port Type C
- 5. USB Port Type 3.2 (2)
- 6. Kensington Lock Slot (At Left Side)
- 7. DisplayPort (2)
- 8. USB Port Type 2.0 (2)
- 9. RJ45 LAN/Fiber LAN (SFP) Ready Options
- 10. 19VDC Power Jack