

10ZiG®

7048q Series Zero Clients



Model Numbers: 7048qv, 7048qc, 7048qm

Industry Leading Secure Endpoint Solutions

The 10ZiG 7048q Series is a flexible, powerful Zero Client workhorse in the 10ZiG hardware lineup. A compact, durable, reliable, and fanless endpoint, the 7048q puts more speed into the Power, Speed, and Performance of 10ZiG and offers superior support for today's modern workforces. Equipped with free centralized management via 10ZiG Manager – cloud-enabled with unlimited user licenses. Covered by a 3-Year Advance Warranty, technical support, and software upgrades. Also available in a Thin Client device.



	Intel J6412 Quad Core 2.00GHz (2.60GHz Burst)
	2 x (3840 x 2160) @ 60Hz via DisplayPort (2 Monitors at 4KUHD*)
	Up to 16GB RAM
	4 x USB 2.0, 2 x USB-3.2, 1 x USB-C (Data Only)
	RJ45 LAN/Fiber LAN (SFP) Ready Options
	TAA Compliant**
	Optional Wireless (Dual External Antenna)
	Supports VESA Mounting and Kensington Lock***
	FREE Centralized Management via 10ZiG Manager™

**TAA compliant on request for EMEA market

***VESA Mounting Bracket required and sold separately

Amazon Workspaces | Apporto | Azure Virtual Desktop | Citrix | ControlUp | Dizzion Frame | Everfox | FabulaTech | HP Anyware | Inuvika | Imprivata | Leostream | Liquidware | Microsoft (AVD / RDS / W365) | Nerdio | Nutanix | Omnisia | Parallels | 90Meter

Americas
EMEA
APAC
DE

P: +1 (866) 865-5250
P: +44 (0) 116 214 8650
P: +61 2 80027421
P: +49 (0) 6724 9304 45


E: info@10ZiG.com
E: info@10ZiG.eu
E: info@10ZiG.com.au
E: vertrieb@10ZiG.de

www.10ZiG.com

7048q Series

Zero Clients



System		Specifications	
Management	10ZiG Manager™	 - Power Button/Power LED - USB Port Type Type C (Data Only) - USB Port Type 3.2 - Headset Jack (TRRS) - USB Port Type 2.0 - DisplayPorts - RJ45 LAN/Fiber LAN (SFP) Ready Options 12V DC Jack - Kensington Lock Slot	
Processor	Intel J6412 Quad Core 2.00GHz (2.60GHz Burst)		
Processor Graphics	Intel HD Graphics		
Dimensions			
Device	1.7" (D) x 6.0" (W) x 7.9" (H) in.		
Weight	3.53 lbs. (1.6 kg.)		
Connections			
Ports on Device	2 x DisplayPort, 4 x USB 2.0, 2 x USB-3.2, 1 x USB-C (Data Only), 1 x DC Jack, 1 x 3.5mm Headset Jack (TRRS)		
Video Resolution	2 x (3840 x 2160) @ 60Hz via DisplayPort (2 Monitors at 4KUHD*)		
Networking			
Wireless	Optional (802.11 a/b/g/n/ac/ax External Antenna)		
Ethernet	10/100/1000 Base-T, RJ45 LAN or Fiber LAN (SFP) Ready Options		
Environmental			
Operating Temp	32°-95°F (0°-35°C), 20-80% non-condensing humidity		

*Note: Actual display performance, such as multi-monitor and higher resolutions including 4K/UHD/QHD/WQHD are dependent upon your current VDI infrastructure and any additional requirements. Consult with 10ZiG for further guidance and model recommendation.

Operating System	7048qv VMware NOS™ (Zero)	7048qc Citrix NOS™ (Zero)	7048qm Microsoft NOS™ (Zero)
Memory (RAM)	Std: 8GB Max: 16GB	Std: 8GB Max: 16GB	Std: 8GB Max: 16GB
Supported Protocols	Blast Extreme, PCoIP, RDP	Citrix ICA, Citrix EDT (HDX)	Azure Virtual Desktop (AVD), RDP, Windows 365
Connection Servers	Horizon, Horizon Security Server, Unified Access Gateway (UAG), Workspace One	Citrix Cloud, Citrix Storefront, Netscaler	Azure Virtual Desktop (AVD), Direct RDP, RD Gateway, RD Load Balancer, RD Web, Windows 365