

10ZiG®

7548qTAA Series Mobile Zero Clients

Model Numbers: 7548qvTAA, 7548qcTAA, 7548qmTAA

Industry Leading Secure Endpoint Solutions

The 10ZiG 7548qTAA Series is a mobile, TAA compliant, Zero Client laptop endpoint with anti-glare display, full-size keyboard & numeric pad, high-definition audio with built-in mic and two speakers, and an HD video camera - for VDI and DaaS on-the-move! Equipped with free centralized management via The 10ZiG Manager, which comes cloud-enabled with unlimited user licenses. Complete with technical support and software upgrades. Also available in a Thin Client device.



Multi-functional #9070 Port Replicator (Docking Station) available and sold separately: ask us!

	Intel Alder Lake N100 6W Quad Core – Turbo Speed to 3.4GHz
	Display 15.6" IPS FHD (1920x1080) Anti-Glare, 16.9 Panel
	8GB DDR4 3200MTs RAM
	128GB M.2 2280 Flash
	3 x USB-A 3.2 Gen1, 1 x USB-C 3.2 Gen1 (DP Alt + PD), 1 x HDMI 1.4, 1 x SD Card Reader
	Up to 8 hours (idle), Up to 4 hours (load)*
	HD Audio & Visual, Built in Mic & Camera
	Intel Dual Band Wireless
	TAA Compliant**
	Supports Kensington Lock
	FREE Centralized Management via 10ZiG Manager™

*Based on an average VDI workload

**TAA compliant on request for EMEA market

Amazon Workspaces | Apporto | Azure Virtual Desktop | Citrix | ControlUp | Dizzion Frame | Everfox | FabulaTech | HP Anyware | Inuvika | Imprivata | Leostream | Liquidware | Microsoft (AVD / RDS / W365) | Nerdio | Nutanix | Omnisia | Parallels | 90Meter

Americas
EMEA
APAC
DE

P: +1 (866) 865-5250
P: +44 (0) 116 214 8650
P: +61 2 80027421
P: +49 (0) 6724 9304 45

E: info@10ZiG.com
E: info@10ZiG.eu
E: info@10ZiG.com.au
E: vertrieb@10ZiG.de

www.10ZiG.com

7548qTAA Series

Mobile Zero Clients



System		Specifications	
Management	10ZiG Manager™		
Processor	Intel Alder Lake N100 6W Quad Core – Turbo Speed to 3.4GHz		
Processor Graphics	Intel UHD Graphics		
Dimensions			
Device	9.6" (D) x 14.5" (W) x 0.85" (H) - In.		
Weight	3.96 lbs. (1.8 kg.)		
Connections		1. Kensington Lock Slot 2. USB Port Type Type C 3.2 Gen1 (DP Alt + PD) 3. HDMI Port 4. USB Port Type A 3.2 Gen1 5. Analog Headphone Jack 6. MicroSD Card Slot 7. USB Port Type A 3.2 Gen1 8. Ethernet Port	
Ports on Device	3 x USB-A 3.2 Gen1, 1 x USB-C 3.2 Gen1 (DP Alt + PD), 1 x HDMI 1.4, 1 x SD Card Reader		
Video Resolution	(1920 x 1080) Anti-Glare		
Integrated Webcam	(1280 X 720) @ 30FPS		
Networking			
Wireless	Intel Dual Band Wireless (a/b/g/n/ac)		
Environmental			
Operating Temp	32°-95°F (0°-35°C)		

Operating System	7548qvTAA VMware NOS™ (Zero)	7548qcTAA Citrix NOS™ (Zero)	7548qmTAA Microsoft NOS™ (Zero)
Memory (RAM)	8GB	8GB	8GB
Supported Protocols	Blast Extreme, PCoIP, RDP	Citrix ICA, Citrix EDT (HDX)	Azure Virtual Desktop (AVD), RDP, Windows 365
Connection Servers	Horizon, Horizon Security Server, Unified Access Gateway (UAG), Workspace One	Citrix Cloud, Citrix Storefront, Netscaler	Azure Virtual Desktop (AVD), Direct RDP, RD Gateway, RD Load Balancer, RD Web, Windows 365